## **EUROPEAN PATEN OFFICE**

## **Patent Abstracts of Japan**

PUBLICATION NUMBER

63215952

**PUBLICATION DATE** 

08-09-88

APPLICATION DATE

05-03-87

APPLICATION NUMBER

62048951

APPLICANT:

MAZDA MOTOR CORP;

**INVENTOR:** 

SASAKI HIDEYUKI;


INT.CL.

G01N 21/88

TITLE

INSPECTION FOR SURFACE

CONDITION



ABSTRACT:

PURPOSE: To achieve a higher detection accuracy, by comparing a first image generated by first reflected light with a short wavelength with a second image generated by second reflected light with a long wavelength to detect a defect on the surface of an object to be detected from a light density difference between the first and second images.

CONSTITUTION: Reflected light from an object to be detected is divided into infrared image F-1 and ultraviolet image F-2 through a high resolution cameras 14 and an LPF 12 to be stored into first and second memories 22a and 22b. Then, the images F-1 and F-2 are subjected to a subtraction processing per pixel by a comparator 24 and after a defect point is detected by a CPU, the processed image F-3 is stored in a third memory 22c or displayed on a CRT 28. In this manner, a higher detection accuracy is achieved for a defect on the surface of the object being detected.

COPYRIGHT: (C)1988,JPO&Japio